

UHF WALKY-TALKY

WPC approved

TK-688

- Voice Association
- PC Programming
- 16 Channels
- 4 Watts
- VOX : In built
- Low Power Alarm
- Transmit Time Limited
- Busy Channel Lock-out
- 12.5/25 Khz Compatibility
- Li-ion Battery Pack



(Actual Size)

Specification

Model	: TK - 688
Frequency Range	: UHF 350-351 MHz
Channel	: 16
Operating Voltage	: 7.4 V DC (Li-ion Battery Pack)
Antenna Impedance	: 50 Ω
Working Temp.	: -30°C ~ +60°C
Weight (w/Battery)	: 250 gm

Compatible w/American Military Standard (MIL-STD-810C/D/E)

Transmitter (EIA-316 B Standard)

RF Power Output	: 4 W
Modulation Type	: F3E
Modulation distortion	: <5% (300 ~ 3000 Hz)
Max Freq. Deviation	: < 5 KHz (1000 KHz when 100%)
FM Noise	: \leq -45 dB
Working Temp.	: -30°C ~ +60°C

Receiver

Sensitivity (12dB SINAD)	: 0.16 V μ V
Selectivity	: 55 dB
Adjacent Channel Selectivity	: \geq 70 dB
Noise Respond	: \geq 60 dB
FM Noise	: 45 dB / 40 dB
Modulation Type	: 16 KOF3E
Audio Distortion	: < 5 %
Operating Bandwidth	: \pm 7 KHz

Accessories

